



## **INTRODUCTION**

The FS column series is the fastest way to get a professional, compact PA system. Considering the column speakers and a high-power subwoofer built-in amplifier, users can expect a system of full-range sound. The most convenient thing is that the FS sound column has a wireless Bluetooth input. The FS column series has two different models to choose from, FS-04 and FS-08.

FS-04 is equipped with a long-stroke 12" subwoofer 4×3" wideband driver. Extend to a lower frequency response and a higher output of 700W peak, which is perfect for corporate speeches and singer-songwriters of this type of performance.

FS-08 is equipped with a long-stroke 12" subwoofer 8×3" wideband driver. Extending to a lower frequency response and a higher output of 1000W peak, if you want more power, the two systems can use a stereo pair, which is connected together through the built-in XLR output.

The built-in mixer of the FS column series provides full control, more than 2×XLR/socket joint input (MIC and line level) plus a phono input to mix and play songs, live vocals and instruments. According to modern technology-savvy DJs and engineers, it is easy to pair with your mobile phone using Bluetooth input in a short time.

## FEATURES

- Light weight, portable active cylindrical PA system; Bluetooth wireless connection
- Canon, socket and RCA phonograph input
- Two systems: 412 & 812
- Diversity, high power 3"high/medium driver (4 or 8)
- 12"Long stroke subwoofer
- Black painted surface
- Through the Canon output, connect a variety of systems; thin wire cable structure

## **FS Series**



#### **SPECIFICATIONS**

Model number	FS-04	FS-08
Types of	Passive full frequency sound column	Passive full frequency sound column
power	Continuous 150W/ program 300W/peak 600W	Continuous 300W/ program 600W/peak 1200W
Frequency response	150Hz-20KHz	140Hz-20kHz
Sensitivity	95	97
Maximum sound pressure level	123dB	124dB
Constant resistance	<b>8</b> Ω	4 Ω
Spread angle	160H x 40V	160H x 40V
input interface	1xSpeakon	1xSpeakon
Wall bracket	Built-in	Built-in
material	12mm MDF	12mm MDF
Woofer		
Bass output power		
input interface		
Output Interface		
AC power		
size	445×116.5×115mm	805×116.5×115mm
net weight	3kg	5.1kg

# **FS Series**